

RN505 TECHNICAL SPECIFICATIONS

TECHNICAL FEATURES:

Suitable materials:	stretch-film
Initial film thickness:	6-30 μ
Mother roll (<i>Jumbo</i>):	
Maximum diameter:	250 mm
Width:	450-500 mm
Core internal diameter:	76.2 mm (3")
Finished roll:	
Maximum diameter:	260 mm
Core length:	450-530 mm
Film width:	450-530 mm
Core internal diameter:	38 mm, 50 mm, 75 mm (1,5", 2", 3")
Mechanical speed:	700 m/min
Production speed:	500 m/min
Installed power:	2 kW
Power supply:	
Primary:	3ph 400V 50 Hz + N + PE
Auxiliary:	24V d c.
Service:	220V
Consumption:	11 kW/h
Compressed air: Pressure:	6bar

RN505 TECHNICAL SPECIFICATIONS

Electrical standards:	CE regulations
Safety standards:	CE regulations
Average noise level:	< 82 dBA
Overall size:	
RND505 (l x w x h):	750 x 1120 x 450 mm
Maximum weight:	320 kg

MAIN ELECTROPNEUMATIC COMPONENTS

Electromechanics:	Delta
PLC:	Delta
Operator pannel:	Delta
Servo motors:	Airtac
Pneumatics:	Airtac